

**Forum: Configuração**

**Topic: SMTP autenticado**

**Subject: Re: SMTP autenticado**

Enviado por: Marcos Abadi

Enviado em: 6/5/2007 22:48:11

No meu main.cf uso os seguintes parâmetros para o sasl:

##### SMTP SASL #####

smtpd\_sasl\_local\_domain =

smtpd\_sasl\_auth\_enable = yes

smtpd\_sasl\_security\_options = noanonymous

broken\_sasl\_auth\_clients = yes

smtpd\_sender\_restrictions = permit\_sasl\_authenticated,

    permit\_mynetworks,

    reject\_non\_fqdn\_sender,

    reject\_unknown\_sender\_domain,

    reject\_unauth\_pipelining

smtpd\_recipient\_restrictions = permit\_sasl\_authenticated,

    permit\_mynetworks,

    check\_recipient\_access hash:/etc/postfix/usuarios-restritos.cf

    check\_sender\_access hash:/etc/postfix/sender\_checks,

    check\_client\_access hash:/etc/postfix/access

    reject\_unauth\_destination,

    reject\_rbl\_client list.dsbl.org,

    reject\_rbl\_client relays.ordb.org,

    reject\_rbl\_client sbl-xbl.spamhaus.org,

    reject\_unauth\_destination,

    reject\_non\_fqdn\_recipient,

    reject\_unknown\_recipient\_domain,

smtpd\_data\_restrictions = reject\_unauth\_pipelining